

PROPELLER MAINTENANCE RECORD

PROPELLER MODEL 76EM8-6-56

PROPELLER SERIAL NUMBER 102236K

TABLE OF PROPELLER ATTACHING BOLT WRENCH TORQUE
Sensenich Metal Propellers (the proper torque is also shown on Blade Information Decal)


PROPELLER SERIES**	BOLT DIA. (inches)	RECOMMENDED WRENCH TORQUE		
		In.-lb.	ft.-lb.	n.-m.
69CK, M69CK (6 bolts)				
72CK (6 bolts)				
74CK, M74CK (6 bolts)				
76AK, M76AK (6 bolts)	3/8 (0.375)	280-300	23-25	32-34
76AM6, M76AM (6 bolts)				
74DM6, M74DM (6 bolts)				
74DR, M74DR (8 bolts)				
74DM7 (6 bolts)	7/16 (0.4375)	480-540	40-45	54-61
72CC, 72FM8 (6 bolts)				
74DC, M74DC (6 bolts)	1/2 (0.500)	720-780	60-65	81-88
76EM8, M76EMM (6 bolts)				
* 80BM8, M80BMM (bolts)				

* Not in production
** These are the basic propeller models. Spacer addition does not affect recommended wrench torque.

DESCRIPTION OF ALL OPERATIONS
PERTAINING TO AIRWORTHINESS DIRECTIVES,
SERVICE BULLETINS, SERVICE LETTERS,
& MINOR ADJUSTMENTS

DATE	TACH TIME	DESCRIPTION OF WORK	SIGNATURE
5-13-2011			
TRF1+	836.0	This propeller was installed on N4130E in new condition. Torque checked & applied.	
TR SN	0.0	Inspected TRF 100hr. in good air worthy condition.	
06.12.2012			
TACH	918.4		
F.T.S.N			
82.4			

DATE 06.12.2012
TACH TIME 918.4
TOTAL TIME 82.4 since new
PSMOH _____
I CERTIFY THAT THIS PROPELLER BEEN INSPECTED IN ACCORDANCE WITH A Annual INSPECTION AND WAS DETERMINED TO BE IN AIRWORTHY CONDITION.


DARREN M. LUTZ A&P 500763952 IA

